

Coxdome Access Rooflight

The Coxdome roof access hatch is designed to allow safe access onto the roof space for inspection purposes. It can also be used as a means of emergency escape. The roof hatch has a 150mm SPLAYED upstand and is operated with use of gas assisted springs.

MATERIAL

- Double or triple polycarbonate layers
- Clear or Opal glazing
- UV Stable PVC-u white Upstand
- Gas assisted spring opening

PERFORMANCE

- U Value 1.7 W/m²K based on triple layer
- 150mm PVC Upstand U-value 1.8 W/m²K
- Class B Non-fragile ACR(M)001:2005
- Sound reduction 22dB

Layer Variant	Number of Layers	Light Transmittance	U-Value
Clear (Double)	2 Layers	77%	2.6 W/m ² K
Diffused (Double)	2 Layers	77%	2.6 W/m ² K
Clear (Triple)	3 Layers	71%	1.7 W/m ² K
Diffused (Triple)	3 Layers	71%	1.7 W/m ² K

Available Sizes

Structural Opening

- 750 x 900
- 800 x 800
- 900 x 900
- 900 x 1200
- 1000 x 1000
- 1000 x 1500
- 1100 x 1100
- 1200 x 1200
- 1200 x 1800

CAD Drawings

